

Factory site: 666 Xiangfu Road, Hangzhou, Zhejiang, China (311305)

Tel: +86-571-88926735 88926755 Fax: +86-571-88926789 88132890

sales@hcforklift.com www.hcforklift.com

HANGCHA GROUP CO., LTD. reserves the right to make any changes without notice concerning colors, equipment, or specifications detailed in this brochure, or to discontinue individual models. The colors of trucks, delivered may differ slightly from those in brochures.



IS045001:2018



YouTube

IS014001:2015







WeChat



Download "Hangcha Forklift" App

IS09001:2015



2024 VERSION 1/COPYRIGHT 2024/03





MORE INNOVATION TO YOUR WORK

MACHINE CHARACTERISTICS

- 460/310kg double load capacity design, larger load, wider range of operation.
- The upper control is configured with 3 proportional control handles, smooth and accurate action, better micromobility.
- Hangcha brand lithium battery, five-year warranty, high quality guarantee, excellent performance, safe and reliable.
- Self weight drop and the electric proportional speed regulation reduce the energy consumption.
- Independent emergency power system, to provide more safety protection.
- Lithium battery is equipped with charging port, support external charger fast charging.
- Controller with large LED screen provides fault self-diagnosis function.

PERMANENT MAGNET MOTOR DRIVE

Energy consumption reduced by more than 10%, strong power, the maximum climbing capacity reaches 45%. It drive variable piston pump, performance is better than the diesel model, could realize two actions simultaneously.





REACHES 45%



With the 12V emergency power system, the operator can be safely returned to the ground even if the main battery out of power.



The front bridge has floating function, make driving more stable on unlevelling land.



Permanent magnet motor drive variable piston pump, strong performance and low energy consumption.



2.44 m large basket, can accommodate 3 people working at the same time. The basket controller is equipped with 3 proportional control handles, and the boom expansion and amplitude variation support simultaneous movements.



Features

Truck	Standard	Options
Hydraulic leveling work platform	•	
Weighing system	•	
Four wheel brakes	•	
180°Hydraulic rotary platform(HB250/280P)	•	
Four wheel drive	•	
Front floating bridge	•	
Emergency descent system	•	
Transport turntable protection lock	•	
Emergency pump station	•	
Anti-extrusion device	•	
AC power line to platform	•	
Platform power socket		0
Lithium battery		0
80V80A High-current vehicle charger		0
External 100 / 200A high-power charger		0
Controls and instruments		
Rear inspection and travelling confirmation	•	
Fault diagnosis system	•	
4.3 inch color screen	•	
Three handles proportional control	•	
Pedal switch	•	
Safety		
Emergency brake release	•	
Emergency stop system	•	
Full tube sheath protection	•	
Horn and buzzer safety warnings	•	
Alarm light safety warning	•	
Tilt protection system	•	
Lights		
Work lights		0